

FIRE EXTINGUISHER

PRODUCT CODE
FXC__

CARBON DIOXIDE



B: FLAMMABLE LIQUIDS



E: ELECTRICAL EQUIPMENT



2.0 kg

3.5 kg

5.0 kg

APPLICATIONS: CO₂ Extinguishers are designed for use on E Class fires, involving energised electrical equipment such as switchboards, electrical motors and electronic equipment. They are also suitable for use on B Class Flammable Liquid fires. CO₂ is a gas that penetrates and spreads to all parts of the fire area. These extinguishers are more effective when used indoors or where wind is not a factor, however they are NOT recommended for use within confined spaces.

CONSTRUCTION: Our CO₂ fire extinguishers feature a lightweight aluminium seamless cylinder which is manufactured to Australian Standards. The robust forged brass chrome plated valves incorporate a pressure relief safety valve, with a stainless steel handle and lever fitted.

Australian Standards Approval AS1841.6

CAPACITY Kg	CYLINDER DIAMETER mm	HEIGHT mm	OVERALL MASS (Approx)	DISCHARGE TIME (Sec)	RATING	MODEL
2.0	110	520	5.2	8	2B:E	FXC20
3.5 with hose	140	570	9.2	9	5B:E	FXC35
5.5 with hose	150	660	12.4	9	5B:E	FXC50

ISSUE 2.0 15-04-08 CS510 FXC