

FIRE HOSE REEL

Heavy Duty c/w Bearing

PRODUCT CODE

HRP3619/HD

DIMENSIONS

Diameter : 555mm

Depth : 245mm

MATERIAL

Side Plates: Mild Steel. Painted Signal red

Spacer Pins: Mild Steel. Zinc Plated

Fire Reel Hose: P.V.C. 19mm Internal Diameter

Standard Hose Length: 36metres

Nozzle: Jet: Lever Action Brass

Guide Arm: Swivel. Zinc Plated

Bracket: Easi-Fit. Galvanised

Barrell Union: F&F. Galvanised

Spindle: Brass

Roller Bearing c/w Stainless Steel Case

Waterway: Brass

Isolation Valve: Brass. 25mm & Nozzle Interlock

INSTALLATION

Drum Centre: 1400 - 2400mm

Isolation Valve Centre: 900 - 1100mm

RECOMMENDATION

Mounting the Isolation Valve at a height of 1060mm will achieve the minimum Hose Reel centre height of 1500mm

If the minimum Isolation Valve height of 900mm is required, the length of the backpipe will need to be extended on site

Radial clearance of not less than 100mm must be maintained around the Hose Reel Plates and Isolating Valve

OPTIONS

Rewind Handle

